





	Verrouillage	Référence					Certification	Poids
<b>Mousquetons aluminium</b>								
<b>WILLIAM</b>	SCREW-LOCK	M36 SL / SLN	25 mm	25 kN	7 kN	7 kN	CE EN 362	90 g
	TRIACT-LOCK	M36 TL / TLN	24 mm					
	BALL-LOCK	M36 BL	24 mm					
<b>Am'D</b>	SCREW-LOCK	M34 SL	21 mm	28 kN	7 kN	8 kN	CE EN 362	75 g
	TRIACT-LOCK	M34 TL	21 mm					
	BALL-LOCK	M34 BL	22 mm					
<b>OK</b>	SCREW-LOCK	M33 SL / SLN	19 mm	24 kN	10 kN	7 kN	CE EN 362	75 g
	TRIACT-LOCK	M33 TL / TLN	19 mm		8 kN			
<b>Mousquetons acier</b>								
<b>OXAN</b>	SCREW-LOCK	M72 SL / SLN	21 mm	27 kN	7 kN	7 kN	CE EN 362, NFPA 1983, Light Use	195 g
	TRIACT-LOCK (normes européennes)	M72 TL	21 mm		7 kN			215 g
	TRIACT-LOCK (normes nord-américaines et européennes)	M72 TLA / TLN	19 mm		16 kN		CE EN 362, ANSI Z359.1, NFPA 1983, Light Use, CSA Z259.12	236 g
<b>VULCAN</b>	SCREW-LOCK	M73 SL / SLN	31 mm	40 kN	11 kN	11 kN	CE EN 362, NFPA 1983, General Use	265 g
	TRIACT-LOCK (normes européennes)	M73 TL	30 mm		11 kN			285 g
	TRIACT-LOCK (normes nord-américaines et européennes)	M73 TLA / TLN	29 mm		16 kN		CE EN 362, ANSI Z359.1, NFPA 1983, General Use, CSA Z259.12	305 g
<b>Mousquetons aluminium spéciaux</b>								
<b>OMNI</b>	SCREW-LOCK	M37 SL / SLN	22 mm	20 kN	15 kN	7 kN	CE EN 362	86 g
	TRIACT-LOCK	M37 TL / TLN	22 mm					92 g
<b>FREINO</b>	TWIST-LOCK	M42	15 mm	25 kN	10 kN	9 kN	CE EN 362	85 g
<b>SPIRIT</b>	-	M15 A	20 mm	23 kN	10 kN	9,5 kN	CE EN 12275 type B	49 g
<b>Connecteur de grande taille</b>								
<b>MGO</b>	Automatique	MGO60	60 mm	25 kN	-	-	CE EN 362	455 g
		MGO110	110 mm	23 kN	15 kN	7 kN	CE EN 362	938 g
<b>Maillons rapides</b>								
<b>DELTA</b>	Maillon rapide	P11	12 mm	25 kN	10 kN	-	CE EN 362 type Q	150 g
		P11-8	10 mm	25 kN	10 kN	-	CE EN 362 type Q	85 g
		P11-8B	10 mm	25 kN	10 kN	-	CE EN 362 type Q	96 g
<b>GO</b>	Maillon rapide	P15	16 mm	25 kN	10 kN	-	CE EN 362 type Q	60 g
<b>DEMI ROND</b>	Maillon rapide	P18	10 mm	25 kN	10 kN	-	CE EN 362 type Q	55 g