



166AA2EU1





Hi-vis rainjacket

100% waterproof / windproof / highly breathable / waterrepellent outer fabric / moisture attracting coating on the inside / very comfortable / supple





Hi-vis rainjacket

Anfield - 166AA2EU1

European Standards:

- » EN ISO 20471: 2013 / Class 3
- » EN 343: 2003 + A1: 2007 / Class 3-3
- » EN ISO 13688: 2013

Exterior:

- » Straight collar
- » Detachable hood with chin protection
- » Zip closure under flap with touch & close fastening
- » 1 inset chest pocket with zip closure
- » 2 inset pockets
- » Round inset sleeves
- » Elasticated wristband with narrowing by touch & close fastening
- » Underarm ventilation
- » Drawstring in waist
- » Taped seams
- » Back length 85 cm (L)

Interior:

- » Fixed lining: mesh in body and polyamide in sleeves
- » Knitted wind cuffs in sleeves
- » 1 inside pocket
- » Zipper in back lining for placing logos

Fabric:

SIOPOR® Ultra: 100% polyester fabric with 100% PU coating; ± 195 g/m²

Sizes:

S - XXXL

Colour:

- » 278 Hi-Vis Yellow/Navy
- » 279 Hi-Vis Orange/Navy

167A (p.116) - 168A (p.151) - 169A (p.117)

Combining products:

5887 (p.153) - 799Z (p.144)

Packaging:

» 10 pieces per box

Wash & Care instructions:











SIOEN head office Fabriekstraat 23 B-8850 Ardooie Belgium T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



Discover our products © 2016 SIOEN - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the SIOEN Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that SIOEN disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.