



3 year guarantee



Patent Pending

ZILLON

**Adjustable lanyard
for work positioning**
Longe réglable
de maintien au travail

CE 0082 EN 358

2,5 m	570 g
4 m	740 g
5,5 m	900 g



⚠ WARNING


Activities involving the use of this equipment are inherently dangerous.
You are responsible for your own actions and decisions.

- Before using this equipment, you must:
 - Read and understand all instructions for use.
 - Get specific training in its proper use.
 - Become acquainted with its capabilities and limitations.
 - Understand and accept the risks involved.

**FAILURE TO HEED ANY OF THESE WARNINGS MAY
RESULT IN SEVERE INJURY OR DEATH.**



Traceability and markings / Traçabilité et marquage



CE 0082

- a. Body controlling the manufacture of this PPE
- b. Notified body that carried out the CE type examination
Apave SudEurope SAS
BP 193 - 13322 Marseille
Cedex 16 - France - N°0082

c. Traceability: datamatrix = product reference + individual number

d. Length

e. Individual number

00 000 AA 0000

f. Year of manufacture

g. Day of manufacture

h. Control or name of inspector

i. Incrementation

j. Standards

k. Carefully read the instructions for use

l. Model identification

PETZL.COM



Latest version



Other languages



Product Experience



PPE checking

Warning symbols Panneaux d'alertes



PETZL
F-38920 Crolles
PETZL.COM
ISO 9001
© Petzl




Sustaining our Community
Au service de la Communauté
FONDATION-PETZL.ORG





100%
Recycled
paper

1. Field of application Champ d'application




3. Inspection, points to verify Contrôle, points à vérifier

PPE checking
Vérification EPI
PETZL.COM




2. Nomenclature Nomenclature




4. Compatibility (text part) Compatibilité (partie texte)

5. Installing the ZILLON
Mise en place de la ZILLON




Choosing an anchor / Choix de l'ancrage




5. Installing the ZILLON
Mise en place de la ZILLON

Connecting the lanyard to the harness / Connexion de la longe au harnais




6. Function principle Principe de fonctionnement


Shorten the lanyard
Raccourcir la longe







Work positioning
Maintien au travail



Extend the lanyard
Aggrandir la longe



7. Precautions for use Précautions d'utilisation




8. Other techniques Autres techniques



Product Experience
PETZL.COM

Spare parts Pièces détachées

L22AR 025



L22AR 040



L22AR 055



9. Additional information Informations complémentaires



A. Lifetime / Durée de vie

Serial n°
00XXX XXX XXXX + 10 years
ans

B. Markings Marquage



C. Acceptable T° T° tolérées

+ 80°C / + 176°F
- 40°C / - 40°F


D. Precautions for use / Précautions d'usage



E. Cleaning - Disinfection / Nettoyage - Désinfection



F. Drying / Séchage



H. FAQ - Contact / Questions - Contact



petzl.com

9. Additional information Informations complémentaires



A. Lifetime / Durée de vie

∞ unlimited

B. Acceptable T° T° tolérées

+ 80°C / + 176°F
- 30°C / - 22°F

C. Precautions for use / Précautions d'usage



D. Cleaning / Nettoyage



E. Drying / Séchage



F. Storage - Transport Stockage - transport



G. Maintenance Entretien



H. Modifications - Repairs Modifications - Réparations



I. FAQ - Contact Questions - Contact



petzl.com

